

C10


Build No. 20180105

PROFILE

Cost-effective, ARM platform based, Centerm C10 offers you PC-like experiences with wide support of Citrix ICA/HDX, VMware PCoIP and Microsoft RDP.

FEATURES

- **Cost-effective**
Low price and high performance with 1080p video supported
- **High reliability, No moving parts**
MTBF 40,000 hours, fanless cooling
- **Low power consumption**
A green product with low power consumption and low CO2 emission
- **Centerm Linux OS installed**
Professional Centerm Linux OS, secure, reliable and easy to use
- **Dual display supported**
Support dual display both in duplicated and extended mode
- **Multiple VDI protocol supported**
Widely supports Citrix ICA/HDX, VMware PCoIP and Microsoft RDP



Connectivity



No.	Name	Icon
1	Mic-in	
2	Line-out	
3	USB 2.0 port	
4	Power button	
5	RJ-45	
6	DVI-I port	
7	DC 5V input	

VESA Mountable



SPECIFICATION

SYSTEM	
Processor	ARM Cortex A9 Dual-Core 1.5GHz
Available Operating System	COS ①
VDI/HSD Support	Citrix Receiver / VMware view / Microsoft RDP 8 Compatible
Management	CCCM
MEMORY	
RAM (DDR3)	1GB
Flash Memory (eMMC)	4GB
DISPLAY	
Port	DVI-I x 1 (DVI-to-VGA adapter included)
Resolution	1920 x 1200 @ 60Hz
Dual Display	Support (extended mode via Y cable)
NETWORK	
LAN	x 1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
WLAN	Optional built-in USB 802.11 b/g/n wireless
I/O PERIPHERAL INTERFACE	
USB 2.0	x 5 (front x 1, rear x 4)
RJ-45	x 1
AUDIO	
Ports	Front: Line-out x 1 , Mic-in x 1, (1/8-inch mini jack)
DIMENSION	
Device	156.4mm x 37mm x 130mm
Packaging	488mm x 108mm x 256mm
Net Weight	0.44 kg
POWER	
Adapter	Worldwide auto-sensing 100-240V AC, 50/60 Hz, 5V/3A DC
Power Consumption	Desktop mode 5.0w, Full load mode 7.0w
MOUNTING	
VESA Bracket	VESA Mounting Kit
Kensington Lock	Built-in Kensington Lock Slot
ENVIRONMENT	
Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

①: Centerm Operating System (Linux).