



Wyse 7030 zero client

High performance zero client
purpose-built for VMware



Meet the Wyse 7030 zero client for VMware.

For virtual desktop environments, the Wyse 7030 PCoIP zero client for VMware delivers workstation-level performance. Its dedicated hardware PCoIP engine delivers the highest level of display performance available for advanced applications, including CAD, 3D solids modeling, video editing and more.

Extremely compact and energy efficient, the 7030 PCoIP zero client is a fully functional VMware View end point that delivers a true PC-like experience with support for up to 4 displays. The 7030 offers the full benefits of an efficient and secure centralized computing environment, like multiple display support, multimedia playback, HD audio and four USB peripheral ports.

Advanced performance. Higher quality.

The Wyse 7030 PCoIP zero client allows you to centrally manage your virtual desktops in a data center while still providing rich multimedia, high-resolution 3D graphics, HD media, and full USB peripheral interoperability locally over a LAN or remotely over a WAN. Optimized compression algorithms operate in real-time to achieve the best possible image quality for the available network bandwidth.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, giving Dell business partners end-to-end support throughout the product lifecycle.

Cool, simple performance

The 7030 PCoIP zero client for VMware draws under 15 watts of power, creating cooler, quieter working environments. Wyse zero clients for VMware receive and decode signals from the PCoIP host to create standard PC interfaces for the display, USB peripherals and audio.



Specifications

Dell Wyse 7030 zero client for VMware

Processor	Teradici TERA2140 PCoIP
Memory	32MB Flash / 512MB RAM DDR3
Power	Worldwide auto-sensing 100–240 VAC, 50/60Hz. power supply. Multifunction power button LED
Power consumption	Less than 15 watts
Security	Built-in Kensington security slot (cable sold separately)
Certifications (Based on US ratings)	VMware Ready, PCoIP Connected
I/O peripheral support	Four DisplayPort ports Four External USB 2.0 ports (2 front, 2 back) Optional four DVI-D ports mutually exclusive with four DisplayPorts
Networking	10/100/1000 Base-T Gigabit Ethernet Optional Fiber SFP Module Ready (Mutually Exclusive with RJ45)
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate One display 2560 x 1600@60Hz, Color Depth: 8, 15, 16 or 24bpp Two displays 2560 x 1600@60Hz, Color Depth: 8, 15, 16 or 24bpp Four displays 1920 x 1200@60Hz, Color Depth: 8, 15, 16 or 24bpp
Audio	Audio In 1/8-inch mini jack, 8-bit microphone Output: 1/8-inch mini jack, full 16-bit stereo, 48KHz sample rate One Line out / speaker 1/8-inch mini jack
Dimensions	Height x Width x Depth 177 mm x 46 mm x 130 mm (6.97 in x 1.81 in x 5.12 in) Weight 0.765kg (1.67lb)
Mountings	Vertical feet
Temperature range	Vertical position, power button up 10° to 40° C (50° to 104° F) Storage -10° to 60° C (14° to 140° F)
Humidity	Condensing 20% to 80% Non-condensing 10% to 95%
Keyboard and mouse	Enhanced USB keyboard with Windows Keys (104 keys) USB optical mouse are also available and sold separately (availability varies by region).
Warranty	3-year limited hardware warranty
Support and deployment	Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.

Learn more: Visit www.dell.com/wyse

Dell Inc.
One Dell Way
Round Rock, TX 78664

Visit our website at:
www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
CCC_sales@dell.com

Dell.com