

When performance and versatility matter

The Wyse 7000 series thin client is for users that demand more from their virtual desktop environments, featuring all the security and management benefits of thin clients.

The Wyse 7020 features a quad core AMD G-Series APU, delivering uncompromising performance with fast, flexible user connectivity and outstanding energy efficiency.

Class-leading connectivity

With so much power and so many familiar peripherals at their fingertips, the busiest knowledge workers and power users will love the Wyse 7000 series. It offers a broad range of fast, flexible connectivity options so one can enjoy their favorite peripherals while working with processing-intensive, graphics-rich applications.

Highly scalable, easy to manage

IT won't need to visit or touch Wyse 7000 series thin clients to manage them as they can be managed remotely with Wyse Device Manager (WDM). WDM helps lower the total cost of ownership for large deployments and offers remote enterprise-wide management that scales as you grow from just a few to tens of thousands of cloud clients.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, giving Dell business partners end-to-end support throughout the product lifecycle.

Smart, environmentally conscious computing

Wyse 7000 series thin clients include extremely efficient processors and a silent, fan-less design that uses as little as 15 watts of power.

Specifications Dell Wyse 7020 thin client Windows Embedded Standard 7/7P/8 Operating system Windows 10 IoT Enterprise, 64 bit Wyse ThinLinux Quad-core AMD GX-420CA 2.0 GHz **CPU** Quad-core AMD GX-415GA 1.5 GHz (Quad Display configuration) 32GB Flash / 4GB RAM DDR3 (Windows 10 IoT Enterprise, WE8S and WES7P 16GB Flash / 4GB RAM DDR3 (Windows Embedded Standard 7) Memory 8GB Flash / 2GB RAM DDR3 (Linux) Optional SSD storage also supported AMD Radeon HD 8400E graphics (integrated with APU) Graphics AMD Radeon HD 8330E and AMD Radeon E6240 (Quad Display configuration) 1 x DisplayPort. (Optional DisplayPort to DVI-I adapter available) 1 x One DVI-I port. DVI to VGA (DB-15) adapter included 4 x USB 2.0 ports (two front, two rear) I/O peripheral support 2 x SuperSpeed USB 3.0 ports on rear (backwards compatible with USB 2.0) Quad Display configuration includes 2 additional DisplayPort interfaces 10/100/1000 Gigabit Ethernet Networking Optional dual band 802.11 a/b/g/n wireless and Bluetooth DisplayPort: 2560x1600@32bpp DVI-I: 1920x1200@32bpp Resolution Dual display: 1920x1200@32bpp 7020 with quad display configuration: up to 3840x2160@32bpp (DisplayPort daisy-chain): Composite audio jack 1/8-inch mini, 16-bit stereo / internal speaker Audio Internal mono speaker Dimensions 7.87 x 1.85 x 8.85 in. (200 x 47 x 225 mm) Weight 2.42 lbs. (1.1 kg) Vertical feet standard / Horizontal feet optional. Mountings Optional wall mounting bracket for mounting to flat surfaces, such as walls. Please note: 7000 series clients cannot mount directly to the backs of monitors. **Device security** Built-in Kensington security slot (cable sold separately) Worldwide auto-sensing 100-240 VAC, 50/60 Hz. Power Energy Star 5.2 Phase V external and EuP compliant power adapter. Average power usage under 15 watts Operating: 50° to 104° F (10° to 40° C), horizontal and vertical positions Temperature range Storage: 14° to 140° F (-10° to 60° C) Humidity 20% to 80% condensing. 10% to 95% non-condensing GerGerman EKI-ITB 2000, ISO 9241-3/-8. cULus 60950, TÜV-GS, EN 60950 Safety certifications FCC Class B, CE, VCCI, C-Tick WEEE, RoHS compliant Energy Star 5.2 & EPEAT Silver certified Warranty Three-year hardware warranty Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service. Support and deployment

Learn more: Visit www.dell.com/wyse

Dell Inc. One Dell Way Round Rock, TX 78664 Visit our website at: www.dell.com/wyse

Ask a Dell expert:

https://marketing.dell.com/t2d-wyse

Dell cloud client-computing sales 1-800-438-9973 CCC_sales@dell.com